



Waffle-Iron Waveguide Filter: (a) view looking into port 2, (b) exploded view.

Prior Art FIG. 1









Examples of resonant vias from Riad's US patent 5,886,597.

Prior Art FIG. 2




Prior Art FIG. 3

	Mechanically-Unbalanced	Mechanically-Balanced
Internal	Internal "T"  US Pat. 5,886,597	Internal "double T"  US Pat. 6,542,342 Internal "T" 
External	External "T"  US Pat. 5,886,597	External "T" 
Hybrid		Hybrid "T" 

Examples of resonant vias. Dielectric layers required for support are not shown.


FIG. 4



The starting point for the derivation of new inventions is the loaded wire media: (a) a single wire with uniform periodic series loads, (b) a rectangular array of loaded wires, (c) loads are now defined as parallel-plate capacitors.


Prior Art

FIG. 5




Exploit the planes of physical symmetry to obtain electromagnetically equivalent structures: (a) the infinite wire media, (b) PPW structures of finite height. The supporting dielectric structure is not shown.

FIG. 6




Alternative embodiments of PPW stop band filters: (a) Capacitive-loaded infinite wire media, (b) a PPW filter of finite height using internal capacitors, (c) PPW filters of finite height using external capacitors. The supporting dielectric structure is not shown.

FIG. 7




Hybrid embodiments include combined internal and external capacitive loads. Dielectric cores are omitted for clarity.

FIG. 8




Elevation view of a square lattice of internal T resonant vias.

FIG. 9




Brillouin zone for a 2D periodic structure with a rectangular lattice of unit cell dimensions $a \times b$ in Cartesian coordinates.

FIG. 10




Dispersion diagram along the ΓX line for the capacitive-loaded wire media corresponding to the array of resonant vias shown in Figure 9. The stop bands are bracketed.

FIG. 11




Dispersion diagram along the ΓM line for the capacitive-loaded wire media corresponding to the array of resonant vias shown in Figure 9. The stop bands are bracketed.

FIG. 12




Geometry for the simulation of the resonant via array shown in Figure 9: (a) plan view showing all 8 cascaded unit cells, (b) top view with upper plate hidden, (c) bottom view with the lower plate hidden.


FIG. 13



(a)



(b)




(c)

Geometry for the simulation of a commensurate period resonant via array of type H12: (a) perspective view showing all 8-cascaded unit cells, (b) plan view, (c) elevation view. Hidden are the dielectric cores in (a), (b) and (c).


FIG. 18

Lossy T20




Transmission response (1901) for a TEM mode propagating in the x direction through the stop band filter shown in Figure 18. A -10 dB stop band is shown from 1.33 GHz to 10.0 GHz, a 7.5:1 ratio.

FIG. 19




Stop band filter embodiment EF_{ext} is well suited for integration into existing PWB designs since it requires neither additional metal layers nor any additional thickness.


FIG. 20



(a)



(b)




(c)

Geometry for the simulation of a commensurate period resonant via array of type H12: (a) perspective view showing all 8-cascaded unit cells, (b) plan view, (c) elevation view. Hidden are the dielectric cores in (a), (b) and (c).


FIG. 18

Lossy T20




Transmission response (1901) for a TEM mode propagating in the x direction through the stop band filter shown in Figure 18. A -10 dB stop band is shown from 1.33 GHz to 10.0 GHz, a 7.5:1 ratio.

FIG. 19



Stop band filter embodiment EF_{ext} is well suited for integration into existing PWB designs since it requires neither additional metal layers nor any additional thickness.

FIG. 20



Plated through holes may be used in the fabrication of resonant vias as illustrated here for an internal I resonant via.

FIG. 21

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.